















ZESTAWIENIE STOLARKI OKIENNEJ															
RODZAJ		stolarka pcv (współczynnik przenikania ciepła 0,9 W/(m²·K)													
OZN. NA RYS.		01	02	03	04	05	06	07	08	0D	OZ9	OZ10	OZ11	OZ12	OW1
SCHEMAT OKNA /WITRYNY															
WYMIARY (mm)	w świetle	1400	1070	1500	1800	1200	1400	1200	1800	800	1500(750+750)	1400	1800(900+900)	900	900
	So muru Ho	1800	1800	1800	1800	700	1200	1800	900	1400	2700(2000+700)	2400	2700(2000+700)	2700(2000+700)	1200
kondyg.	POZIOM 0	-	-	-	-	-	-	-	-	-	-	-	-	-	-
	POZIOM 1	6	7	12	2	2	-	1	-	-	2	-	1	2	2
	POZIOM 2	7	8	-	-	-	-	3	1	17	-	1	-	-	-
	POZIOM 3	-	-	-	-	-	10	-	-	2	-	1	-	-	-
OGÓŁEM SZT.		13	15	12	2	2	10	4	1	19	2	2	1	2	2
UWAGI:														1 szt. LEWE 1 szt. PRAWĘ	1/2 podnoszone